

TK-D240/D340

DMR

VHF/UHF Digital Transceiver

FleetSync®



Ergonomically styled yet tough enough to comply with both MIL-STD and IP54/55 environmental standards, these portables provide the features and performance needed for a wide range of workplaces – from warehouses and stations to shops and hotels. As well as handling both analog and digital communications, these user-friendly DMR radios can even operate in direct mode, without a repeater. They also offer such KENWOOD added value as Call Interrupt and 1-watt audio output. These truly resourceful team members will enable you to make the most of your legacy analog equipment while also benefitting from digital communications.

Two-Slot TDMA

Belonging to the DMR Tier II category, which covers licensed conventional systems, these radios are specified for 2-slot Time Division Multiple Access (TDMA) operation in 12.5 kHz channels. This means they can offer greater spectrum efficiency.

Two-In-One - Digital & Analog

These DMR radios can operate in both digital and FM analog modes, switching automatically as needed. Interoperability with legacy analog radios allows organizations to migrate to full digital at their own pace.

Dual-Slot Direct Mode

Up to two simultaneous subscriber calls can be supported in a 12.5 kHz channel, without requiring a base station or repeater, thus doubling channel capacity.

Call Interruption

In an emergency or whenever a user needs to interrupt a call, Call Interruption is available in both direct and repeater modes, while encoding or decoding. There is also a Lone Worker function to protect employees working alone.

Tough All-Terrain

These portable radios conform to MIL-STD C/D/E/F/G standards for ruggedness, and are IP54/55 rated for dust & water protection, making them more than capable of withstanding harsh operating conditions.

Longer Battery Life

Battery life is always important for radio users. Both Lithium-ion and Ni-MH rechargeable batteries are available. Regardless of battery type, operating hours are longer in digital mode.

Clear, Powerful Audio

A radio's most important quality is clarity – being able to hear, loud and clear, what the other party is saying. And these portables deliver just that. For a start, there is 1 W of audio output power, while the AMBE+2™ VOCODER technology accurately replicates natural human speech nuances for superior voice quality, even with high levels of ambient noise. Additionally, Voice Announcement can confirm the channel number, so there is no need to look at the display. English is the default language, but Spanish and French are also available.

Slim Styling

Compact form with ergonomically stylish design make these radios easy to grip and operate.

Other Features

- Max. 32 ch in 2 zones (16 ch per zone) • Wide 70 MHz UHF coverage • Selectable 8- or 16-channel using channel stopper • 5/1 W (VHF), 4/1 W (UHF) output • Audio output power 1 W @ 12 Ω
- Scanning functions • Password protection (read/overwrite) • Minimum volume setting
- Embedded message • Selective call alert LED
- Key lock • Late entry • Analog signalling: QT/DQT, FleetSync, 2-tone (available later)
- Compander per channel • Squelch level

TKR-D710/D810

VHF/UHF DIGITAL REPEATER



KTI-5
INTERFACE BOX

- DMR Tier II Compatible Air Interface • DMR Digital Conventional & FM Analog Conventional modes • 136-174 MHz, 50-5 W; 450-520 MHz, 40-5 W; 400-470 MHz, 40-5 W
- 30 Channel Capacity • 6 Backlit Programmable Function Keys • Two-digit LED Display • Conventional IP Network* • AIS IP Console Interface*

*Requires Interface Box KTI-5 installed with the IP Network Software.
Note: The TKR-D710/D810 is not compatible with duplex/simplex base operation but only for repeater operation.

Options

<ul style="list-style-type: none"> KNB-29N Ni-MH Battery Pack (1,500mAh) KNB-45L 2,000mAh/7.4V Li-Ion Battery Pack KNB-69L 2,550mAh/7.4V Li-Ion Battery Pack KSC-35SK Fast Charger For the KNB-45L/69L (3-Hour) KSC-43K Dual Chemistry Fast Charger For the KNB-29N/45L/69L KVC-22 DC Vehicular Charger Adapter KRA-22 VHF Low Profile Helical Antenna 	<ul style="list-style-type: none"> KRA-23 UHF Low Profile Helical Antenna KRA-26 VHF Helical Antenna KRA-27 UHF Whip Antenna KRA-41 VHF Stubby Antenna KRA-42 UHF Stubby Antenna KMC-21 Compact Speaker Microphone KMC-45D Speaker Microphone 	<ul style="list-style-type: none"> KEP-2 Earphone Kit for KMC-45D (2.5mm plug) KHS-7 Single Muff Headset KHS-8BL 2-Wire Palm Mic with Earphone (Black) KHS-22 Behind-the-head Headset with PTT KHS-23 2-wire Palm Mic KHS-25 D-Ring Ear Hanger with PTT & Boom Mic 	<ul style="list-style-type: none"> KHS-26 Earbud In-line PTT Headset KHS-27 D-Ring In-line PTT Headset KHS-31C C-Ring PTT Ear Hanger Headset KMB-28 Six Unit Charger Adapter (for six KSC-35SK chargers) (chargers not included) KBH-10 Belt Clip KLH-187 Nylon Case
--	---	--	--

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

GENERAL		TK-D240K	TK-D340K
Frequency Range	Type 1 Type 2	136-174 MHz	450-520 MHz 400-470 MHz
Number of Channels		32	32
Zones		2	2
Max. Channels per Zone		16	16
Channel Spacing	Analog Digital	25 kHz / 12.5 kHz 12.5 kHz	25 kHz / 12.5 kHz 12.5 kHz
Operating Voltage		7.5V DC ± 20%	
Battery Life (5-5-90 battery saver off)		Approx. 11.5/13.5 hrs w/KNB-45L Approx. 14/17 hrs w/KNB-69L	
Operating Temperature Range* with KNB-45L/69L		-22° F ~ +140° F (-30° C ~ +60° C) 14° F to +140° F (-10° C to +60° C)	
Frequency Stability		± 2.0 ppm ± 1.0 ppm	
Antenna Impedance		50 Ω	
Dimensions (W x H x D) Projections Not Included	with KNB-45L with KNB-69L	2.13 x 4.78 x 1.33 in (54 x 121.4 x 33.8 mm) 2.13 x 4.78 x 1.49 in (54 x 121.4 x 37.8 mm)	
Weight (net)	with KNB-45L with KNB-69L	10.0 oz (285 g) 10.9 oz (310 g)	

RECEIVER		TK-D240K	TK-D340K
Sensitivity	Digital (1% BER) Digital (5% BER) Analog (12 dB SINAD)	0.45 µV 0.3 µV 0.25 µV	0.45 µV 0.3 µV 0.25 µV
Selectivity	Analog @ 25 / 12.5 kHz	74 / 68 dB	74 / 68 dB
Intermodulation Distortion	Analog	72 dB	72 dB
Spurious Response	Analog	70 dB	70 dB
Audio Distortion		Less than 10%	
Audio Output		1 W / 12 Ω (Internal Output) 500mW / 8 Ω (External Output)	
TRANSMITTER			
RF Power Output	High / Low	5/1 W	4/1 W
Spurious Response		70 dB	70 dB
FM Hum & Noise	Analog @ 25 / 12.5 kHz	45 / 40 dB	45 / 40 dB
Audio Distortion		Less than 2%	
Emission Designator		16K0F3E, 14K0F2D, 14K0F3E, 12K0F2D, 11K0F3E, 7K50F2D, 7K60FXE, 7K60FXD	

Analog measurements made per TIA 603 and specifications shown are typical. Analog 25 kHz is not included in the models sold in the USA or US territories. Due to advancements in technology, specifications are subject to change without notice. Details and timing of firmware and software updates are subject to change without notice.

FleetSync® is a registered trademark of JVCKENWOOD Corporation.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
All other trademarks are the property of their respective holders.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54/55*				

*1: The 2-pin connector cover has to be connected to the radio, or the locking bracket has to be attached to the KMC-45D external speaker microphone.

KENWOOD

JVCKENWOOD USA Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCKENWOOD Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca

Avionic, safe and customer service
Two way radio and telecommunication technology

AVIONIC SERVICE GmbH / SH
L. Calsonic-Str. 6/E. Viel L. Edelmet | I-39100 Bozen / Bolzano
Tel. +39 0471 506 963 | Fax +39 0471 921 418
info@avionic-service.eu | avionic@pec.it | www.avionic-service.eu

ISO 9001
QUALITY SYSTEM

UKAS
MANAGEMENT SYSTEMS

JQA-1205 091

ISO9001 Registered
JVCKENWOOD Corporation