© 2020 OELMANN ELEKTRONIK GMBH





Features

- Rugged and waterproof
- High receiving sensitivity and selectivity
- 64 POCSAG RICs for user profile / 16 user profiles
- Highly compact, ergonomic and comfortable
- Large and bright high-res graphic display
- Customizable text size for better readability
- Displays information according to the device position
- RGB-color backlight
- Professional high and clear alarm sound level
- Magnet mounted charging USB-cable

Technical data

POCSAG Frequency range	VHF 143158, 158174 MHz
	UHF 442470 MHz
Sensitivity, body- worn	2,0 / 2,5 / 3,2 µV/m (512/1200/2400 Baud)
RF channels	4 per user profile (scan mode)
POCSAG	512, 1200, 2400 Baud
User profiles	16 / user assigned RICs
Addressing	64 RICs with 4 sub-addresses each, frame independent, with programmable RIC-alias (32 characters and assigned alert sound pattern)
Alert	Loud audible alert / priority alert / vibro mode
Incoming messages	 Up to 100, non-volatile. Tone-only, numeric, alphanumeric.
Display	fully graphic, rotatable, 3 font sizes,> 200 characters / page
Battery	Li-Ion rechargeable battery, standard Oelmann Viper type
Measurements	80 x 54 x 18 mm / 80 g with battery
Environmental	—10+55°C / IP67

Professional ultra-portable versatile digital pager

- Wireless alarming and text notifications with sound, light, color, vibration
- Governmental, corporate, public and personnel security services, transport and utilities, safety and healthcare, industries, oil and gas
- 👂 High operational reliability

Options*

- 128 bit (BOS PV) / AES 256 bit (BOSKRYPT)
- Emergency alert top button
- Inductive beacon detector
- Man-down sensor
- GPS receiver
- Bluetooth
- WiFi
- GSM
- Hardware sound module for custom alerts and voice announcements, mp3

Accessories

- Travel, desktop single and multi chargers
- Desktop docking station with external antenna,
- relay output connector, alarm-activated USB output
- Belt clip holster, belt clip pouch case
- Li-lon spare rechargeable battery
- Programming kit

Standard delivery contents

- LX7 pager
- Li-Ion rechargeable battery
- USB charging cable
- Operation manual

Specifications are subject to change without notice to improve reliability, function or design

Original Oelmann radio base stations with gateways to external telecommunication networks, as well as scalable operator's messaging software are available.

Avionic sale and customer service Two-way radio and telecommunication technology







AVIONIC SERVICE GmbH / Srl L.-Galvani-Str. 6/E Via L. Galvani | 1-39100 Bozen / Bolzano Tel. +39 0471 506 963 | Fax +39 0471 921 418 info@avionic-service.eu | avionic@pec.it | www.avionic-service.eu

^{*}Factory assemblies / to be specified when ordering